

**Surface mount transient voltage suppressor power 600 watts**

**Stand-Off Voltage : 5.0V~440V**

**FEATURES**


- For surface mounted applications in order to optimize board space.
- Low profile package
- Glass passivated junction
- Low inductance
- Plastic package has Underwriters Laboratory Flammability

**MECHANICAL DATA**

- Case: SMB
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.055g / 0.002oz

**PINNING**

PIN	DESCRIPTION
1	Cathode
2	Anode



**Maximum Ratings and Electrical characteristics**

**Ratings at 25 °C ambient temperature unless otherwise specified.**


Parameter	Symbol	Value	Unit
Peak Pulse Power Dissipation on 10/1000 s waveform (Note1,Note2, Fig.1).	$P_{PPM}$	600	W
Peak Forward Surge Current, 8.3ms Single Half Sine-Wave Superimposed on Rated Load, (JEDEC Method) (Note 3, Fig4).	$I_{FSM}$ (UNI)	100	A
Peak Pulse Current on 10/1000 us waveform (Note 1, Fig 3)	$I_{PPM}$	see Table 1	A
Typical Junction capacitance at VR=4V, f=1MHz	$C_J$	390	pF
ESD Voltage per IEC6100-4-2 Contact Air	$V_{ESD1}$ $V_{ESD2}$	$\pm 30$ $\pm 30$	kV
Typical Thermal Resistance Junction to Ambient(Note 2)	$R_{\theta JA}$	100	°C/W
Operating Junction Temperature and Storage Temperature Range	$T_j, T_{stg}$	-65 ~ +150	°C

**NOTES:**


1. Non-repetitive current pulse, per Fig.3 and derated above  $T_A = 25^\circ\text{C}$  per Fig. 2.
2. Mounted on 5 mm<sup>2</sup> (0.13mm thick) land areas.
3. Measured on 8.3ms, single half sine-wave or equivalent square wave, duty cycle=4 pulses per minute maximum.
4. Peak pulse power waveform is 10/1000µS.

Type		Reverse Stand-off Voltage	Breakdown Voltage		Test Current	Maximum Reverse Leakage	Max. Clamp Voltage	I <sub>PP</sub>	Package		
			V <sub>BR</sub> @ I <sub>T</sub>						SMB		
		UNI	BI	V <sub>RMW</sub>	Min	Max	I <sub>T</sub>	V <sub>C</sub> @ I <sub>PP</sub>	I <sub>PP</sub>	Device Marking Ccode	UNI
<b>600W Transient Voltage Suppresso</b>											
SMBJ5.0A	SMBJ5.0CA	5	6.4	7	10	800	9.2	65.3	KE	AE	
SMBJ6.0A	SMBJ6.0CA	6	6.67	7.37	10	800	10.3	58.3	KG	AG	
SMBJ6.5A	SMBJ6.5CA	6.5	7.22	7.98	10	500	11.2	53.6	KK	AK	
SMBJ7.0A	SMBJ7.0CA	7	7.78	8.6	10	200	12.0	50.0	KM	AM	
SMBJ7.5A	SMBJ7.5CA	7.5	8.33	9.21	1	100	12.9	46.6	KP	AP	
SMBJ8.0A	SMBJ8.0CA	8	8.89	9.83	1	50	13.6	44.2	KR	AR	
SMBJ8.5A	SMBJ8.5CA	8.5	9.44	10.4	1	20	14.4	41.7	KT	AT	
SMBJ9.0A	SMBJ9.0CA	9	10	11.1	1	10	15.4	39.0	KV	AV	
SMBJ10A	SMBJ10CA	10	11.1	12.3	1	5	17.0	35.3	KX	AX	
SMBJ11A	SMBJ11CA	11	12.2	13.5	1	1	18.2	33.0	KZ	AZ	
SMBJ12A	SMBJ12CA	12	13.3	14.7	1	1	19.9	30.2	LE	BE	
SMBJ13A	SMBJ13CA	13	14.4	15.9	1	1	21.5	28.0	LG	BG	
SMBJ14A	SMBJ14CA	14	15.6	17.2	1	1	23.2	25.9	LK	BK	
SMBJ15A	SMBJ15CA	15	16.7	18.5	1	1	24.4	24.6	LM	BM	
SMBJ16A	SMBJ16CA	16	17.8	19.7	1	1	26.0	23.1	LP	BP	
SMBJ17A	SMBJ17CA	17	18.9	20.9	1	1	27.6	21.8	LR	BR	
SMBJ18A	SMBJ18CA	18	20	22.1	1	1	29.2	20.6	LT	BT	
SMBJ20A	SMBJ20CA	20	22.2	24.5	1	1	32.4	18.6	LV	BV	
SMBJ22A	SMBJ22CA	22	24.4	26.9	1	1	35.5	16.9	LX	BX	
SMBJ24A	SMBJ24CA	24	26.7	29.5	1	1	38.9	15.5	LZ	BZ	
SMBJ26A	SMBJ26CA	26	28.9	31.9	1	1	42.1	14.3	ME	CE	
SMBJ28A	SMBJ28CA	28	31.1	34.4	1	1	45.4	13.3	MG	CG	
SMBJ30A	SMBJ30CA	30	33.3	36.8	1	1	48.4	12.4	MK	CK	
SMBJ33A	SMBJ33CA	33	36.7	40.6	1	1	53.3	11.3	MM	CM	
SMBJ36A	SMBJ36CA	36	40	44.2	1	1	58.1	10.4	MP	CP	
SMBJ40A	SMBJ40CA	40	44.4	49.1	1	1	64.5	9.3	MR	CR	
SMBJ43A	SMBJ43CA	43	47.8	52.8	1	1	69.4	8.7	MT	CT	
SMBJ45A	SMBJ45CA	45	50	55.3	1	1	72.7	8.3	MV	CV	
SMBJ48A	SMBJ48CA	48	53.3	58.9	1	1	77.4	7.8	MX	CX	
SMBJ51A	SMBJ51CA	51	56.7	62.7	1	1	82.4	7.3	MZ	CZ	
SMBJ54A	SMBJ54CA	54	60	66.3	1	1	87.1	6.9	NE	DE	
SMBJ58A	SMBJ58CA	58	64.4	71.2	1	1	93.6	6.5	NG	DG	
SMBJ60A	SMBJ60CA	60	66.7	73.7	1	1	96.8	6.2	NK	DK	
SMBJ64A	SMBJ64CA	64	71.1	78.6	1	1	103.0	5.9	NM	DM	
SMBJ70A	SMBJ70CA	70	77.8	86	1	1	113.0	5.3	NP	DP	
SMBJ75A	SMBJ75CA	75	83.3	92.1	1	1	121.0	5.0	NR	DR	
SMBJ78A	SMBJ78CA	78	86.7	95.8	1	1	126.0	4.8	NT	DT	
SMBJ85A	SMBJ85CA	85	94.4	104	1	1	137.0	4.4	NV	DV	
SMBJ90A	SMBJ90CA	90	100	111	1	1	146.0	4.1	NX	DX	
SMBJ100A	SMBJ100CA	100	111	123	1	1	162.0	3.7	NZ	DZ	
SMBJ110A	SMBJ110CA	110	122	135	1	1	177.0	3.4	PE	EE	
SMBJ120A	SMBJ120CA	120	133	147	1	1	193.0	3.1	PG	EG	
SMBJ130A	SMBJ130CA	130	144	159	1	1	209.0	2.9	PK	EK	
SMBJ150A	SMBJ150CA	150	167	185	1	1	243.0	2.5	PM	EM	
SMBJ160A	SMBJ160CA	160	178	197	1	1	259.0	2.3	PP	EP	
SMBJ170A	SMBJ170CA	170	189	209	1	1	275.0	2.2	PR	ER	
SMBJ180A	SMBJ180CA	180	201	222	1	1	292.0	2.1	PT	ET	
SMBJ188A	SMBJ188CA	188	209	231	1	1	304.0	2.0	PB	EB	
SMBJ200A	SMBJ200CA	200	224	247	1	1	324.0	1.9	PV	EV	
SMBJ220A	SMBJ220CA	220	246	272	1	1	356.0	1.7	PX	EX	
SMBJ250A	SMBJ250CA	250	279	309	1	1	405.0	1.5	PZ	EZ	
SMBJ300A*	SMBJ300CA*	300	335	371	1	1	486.0	1.3	QE	FE	
SMBJ350A*	SMBJ350CA*	350	391	432	1	1	567.0	1.1	QG	FG	
SMBJ400A*	SMBJ400CA*	400	447	494	1	1	648.0	0.9	QK	FK	
SMBJ440A*	SMBJ440CA*	440	492	543	1	1	713.0	0.9	QM	FM	


**Fig.1 Peak Pulse Power Rating Curve**




**Fig.2 Forward Current Derating Curve**



**Fig.3 Pulse Waveform**




**Fig.4 Maximum Non-Repetitive Peak Forward Surge Current**



**PACKAGE OUTLINE**

Plastic surface mounted package; 2 leads

**SMB**



**The recommended mounting pad size**

