


Low Capacitance Bidirectional TVS/ESD Protection Diode**DESCRIPTION**

The ESD3B3CM is designed to protect voltage sensitive components from ESD and transient voltage events. Excellent clamping capability, low leakage, and fast response time, make these parts ideal for ESD protection on designs where board space is at a premium. Because of its small size, it is suited for use in cellular phones, portable devices, digital cameras, power supplies and many other portable applications where board space comes at a premium. Also because of its low capacitance, it is suited for use in high frequency designs such as high speed line applications.

This device has been specifically designed to protect sensitive components which are connected to data and transmission lines from overvoltage caused by ESD (electrostatic discharge), and EFT (electrical fast transients).

**FEATURES**

- ESD per IEC 61000-4-2 ±30 kV (Contact)
- ESD per IEC 61000-4-2 ±30 kV (Air)
- IEC61000-4-4 (EFT) 40A (5/50ns)
- Peak power dissipation: 500W (8/20µs)
- Protects one Vcc or data line
- Low clamping voltage
- Working voltages : 3.3V
- Low leakage current
- Low capacitance

APPLICATIONS

- Cell Phone Handsets and Accessories
- Microprocessor based equipment
- Personal Digital Assistants (PDA's)
- Notebooks, Desktops, and Servers
- Portable Instrumentation
- Networking and Telecom
- Serial and Parallel Ports
- Peripherals

MACHANICAL DATA

- SOD-323 package
- Flammability Rating: UL 94V-0
- High temperature soldering guaranteed: 260°C/10s
- Packaging: Tape and Reel
- Reel size: 7 inch

Low Capacitance Bidirectional TVS/ESD Protection Diode
ABSOLUTE MAXIMUM RATING





Symbol	Parameter	Value	Units
V _{ESD}	ESD per IEC 61000-4-2 (Contact)	±30	kV
	ESD per IEC 61000-4-2 (Air)	±30	
P _{PP}	Peak Pulse Power (8/20μs)	500	W
T _{OPT}	Operating Temperature	-55~150	°C
T _{STG}	Storage Temperature	-55~150	°C

ELECTRICAL CHARACTERISTICS (T_{amb}=25°C)

Symbol	Parameter	Test Condition	Min	Typ	Max	Units
V _{RWM}	Reverse Working Voltage				3.3	V
V _{BR}	Reverse Breakdown Voltage	I _T = 1mA	4.0		6.0	V
I _R	Reverse Leakage Current	V _{RWM} = 3.3V			1.0	μA
V _C	Clamping Voltage	I _{PP} = 1A, t _p = 8/20μs			6.5	V
V _C	Clamping Voltage	I _{PP} = 28A, t _p = 8/20μs		13	18	V
C _J	Junction Capacitance	V _R = 0V, f = 1MHz		38	45	pF


Low Capacitance Bidirectional TVS/ESD Protection Diode

ELECTRICAL CHARACTERISTICS CURVE




Low Capacitance Bidirectional TVS/ESD Protection Diode

SOD-323 PACKAGE OUTLINE DIMENSIONS




Symbol	Dimensions In Millimeters	
	Min	Max
A		1.00
A1	0.000	0.100
A2	0.800	0.900
b	0.250	0.350
c	0.080	0.150
D	1.200	1.400
E	1.600	1.800
E1	2.500	2.700
e	1.800	2.040
L	0.475 REF	
L1	0.250	0.400
θ	0°	8°



Recommended Pad outline

Marking



Ordering information

Order code	Package	Base qty	Delivery mode
ESD3B3CM	SOD-323	3000	Tape and reel